

SECTION 1 – EXTERIOR BACKSTOP PADDING**PART 1 – GENERAL****1.1 SUMMARY**

1. 2” Backstop Padding, 2” Flap Top and Bottom with Grommets

PART 2 – PRODUCTS**2.1 ACCEPTABLE MANUFACTURERS**

- A. Manufacturer: Subject to compliance with requirements, provide products from the following:
 1. Artistic Coverings Inc., (562) 404-9343 or (877) 599-9343, 16444 Manning Way, Cerritos, Ca 90703, www.artisticcoverings.com

2.2 MATERIALS

- A. Vinyl Covering: 18oz coated vinyl, Fabric: 1000x1300 Denier Polyester Basic Fabric, Tear Strength 100x100, Strip Tensile: 300x300, Grab Tensile: 410x410, Anti Fungal, Fire Resistant. Colors are per manufacturer’s standard selection, as selected by Architect.
- B. Filler Foam for Backstop Padding: 2” thick polyurethane foam, Indention load deflection: 95 lbs
- C. Attachment: #0 Brass Grommets placed every 2 foot.

2.3 MANUFACTURED UNITS

- A. Backstop Pads: Provide sewed units that are folded in 2’ sections filled with foam and made with a 2” flap top and bottom with grommets. Mount to wall with masonry or wood anchors (not included) at top 2” top lip and 2” bottom lip, or nylon ties for chain link fencing.

PART 3 – EXECUTION

- A. General: Install per manufacturer’s recommendations and approved shop drawings.