

SECTION 1 – INTERIOR WALL PADS

PART 1 – GENERAL

1.1 SUMMARY

1. 2” Wall padding, wood backed, 1” Lip Top and Bottom

PART 2 – PRODUCTS

2.1 ACCEPTABLE MANUFACTURERS

- A. Manufacturer: Subject to compliance with requirements, provide products from the following:
 1. Artistic Coverings Inc., (562) 404-9343 or (877) 599-9343, 16444 Manning Way, Cerritos, Ca 90703, www.artisticcoverings.com

2.2 MATERIALS

- A. Backing: 7/16” OSB (Oriented Strand Board)
- B. Vinyl Covering: 18oz coated per sq yard vinyl, Fabric: 1000 x 1300 Denier Polyester Basic Fabric, Tear Strength 100x100, Strip Tensile: 300x300, Grab Tensile: 410x410, Anti Fungal, Flame Resistant. Colors are per manufacturer’s standard selection, as selected by Architect. Vinyl cover is wrapped around to the backside of the panel and stapled to the backing material using galvanized steel staples.
- C. Filler Foam for Wall Pads: 2” thick Combo Foam 1 3/8” polyethylene foam and 5/8” 100 ILD Polyurethane foam.

2.3 MANUFACTURED UNITS

- A. Wall Pads: Provide units that are backed with 7/16” OSB with vinyl covering stretched over filler foam, and stapled to back of panel. Mount to wall with wall anchors (not included) at top 1” top lip and 1” bottom lip.

PART 3 – EXECUTION

- A. General: Install per manufacturer’s recommendations and approved shop drawings.