

## SECTION 1 – INTERIOR WALL PADS

### PART 1 – GENERAL

#### 1.1 SUMMARY

1. 2” Wall padding, wood backed, “Z” clip mounted

### PART 2 – PRODUCTS

#### 2.1 ACCEPTABLE MANUFACTURERS

- A. Manufacturer: Subject to compliance with requirements, provide products from the following:

1. Artistic Coverings Inc., (562) 404-9343 or (877) 599-9343, 16444 Manning Way, Cerritos, Ca 90703, [www.artisticcoverings.com](http://www.artisticcoverings.com)

#### 2.2 MATERIALS

- A. Backing: 7/16” OSB (Oriented Strand Board)
- B. Vinyl Covering: 18oz coated vinyl, Fabric: 1000x1300 Denier Polyester Basic Fabric, Tear Strength 100x100, Strip Tensile: 300x300, Grip Tensile 410x410, Anti Fungal, Fire Resistant. Colors are per manufacturer’s standard selection, as selected by Architect. Vinyl cover is wrapped around to the backside of the panel and stapled to the backing material using galvanized steel staples.
- C. Filler Foam for Wall Pads: 2” thick Combo Foam 1 3/8” Polyethylene foam and 5/8” 100 ILD Polyurethane foam.
- D. “Z” Clip: 18 gauge. Galvanized Aluminum, mounted to panel using 5/16” x 1” galvanized bolts screwed into 1/2” threaded t bolts.

#### 2.3 MANUFACTURED UNITS

- A. Wall Pads: Provide units that are backed with 7/16” OSB with vinyl covering stretched over filler foam, and stapled to back of panel. Mount to wall with “Z” Clips at the top and 1” Lip at the bottom attached using wood or masonry hardware (not included).

### PART 3 – EXECUTION

- A. General: Install per manufacturer’s recommendations and approved shop drawings.