

**SECTION 1 – INTERIOR CLASS “A” FR WALL PADS****PART 1 – GENERAL****1.1 SUMMARY**

1. 2” Class “A” Wall padding, wood backed, “Z” clip mounted

**PART 2 – PRODUCTS****2.1 ACCEPTABLE MANUFACTURERS**

- A. Manufacturer: Subject to compliance with requirements, provide products from the following:
  1. Artistic Coverings Inc., (562) 404-9343 or (877) 599-9343, 16444 Manning Way, Cerritos, Ca 90703, [www.artisticcoverings.com](http://www.artisticcoverings.com)

**2.2 MATERIALS**

- A. Backing: 7/16” OSB (Oriented Strand Board)
- B. Vinyl Covering 16oz FR Vinyl: Flame retardant for the life of the fabric; resists internal and external mildewing; rot and fungus resistant. Colors are per manufacturer’s standard selection, as selected by Architect. Vinyl cover is wrapped around to the back side of the panel and stapled to the backing material using galvanized steel staples.
- C. Filler Foam for Wall Pads: 2” thick polymerized open cell foam. Density (lb/ft;pcf) 6.0 –7.0 ASTM D3574A; IFD-25%R (lb/50in) 35 -55 ASTM D3574B
- D. “Z” Clip: 18 gauge. Galvanized Aluminum, mounted to panel using 5/16” 3 prong Zinc T-Nut and Zinc ½” bolts.

**2.3 MANUFACTURED UNITS**

- A. Wall Pads: Provide units that are backed with 7/16” OSB with vinyl covering stretched over filler foam, and stapled to back of panel. Mount to wall with “Z” Clips at the top and 1” Lip at the bottom attached with appropriate wood or masonry fastener (not included).

**PART 3 – EXECUTION**

- A. General: Install per manufacturer’s recommendations and approved shop drawings.